

2019 EXPEDITION® SPORT

PACKAGE HIGHLIGHTS

- Rotax® 600 ACE™ engine with 420W magneto
- REV-XS™ platform
- SC™-5U articulating rear suspension
- Locking mechanism on one side (no tool required) for articulated suspension
- 406 x 3,923 x 38.1 mm (16 x 154 x 1.5 in.) Charger track
- Adjustable ski stance
- Brembo brake with braided stainless-steel brake line
- Mechanical reverse
- Heated driver's visor power outlet
- Rack & Hitch
- 2-up seat with backrest
- D.E.S.S.™ key
- Extended heat exchanger for better cooling capacity
- iTC™ Engine mapping modes (Standard, Sport or ECO®)
- Reversible throttle lever (thumb or finger activated)
- Air radiator with fan & engine oil cooler
- Heavy duty rear bumper



ROTAX® ENGINE

600 ACE™

Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2
Displacement	600 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7,250 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	40 L
Oil tank capacity	2.1 L

POWERTRAIN

Drive clutch type	eDrive™ 2
Driven clutch type	QRS (short shaft)
Engagement	2,200 RPM
Small sprocket number of teeth	21
Large sprocket number of teeth	51
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm
Brake system	Brembo brake with stainless-steel braided brake line

DRY WEIGHT

244 kg

COLOR

White ☐

DIMENSIONS

Vehicle overall length	3,247 mm
Vehicle overall width	1,140 to 1,180 mm
Vehicle overall height	1,275 mm
Ski stance	975 or 1,020 mm
Ski overall length	1,049 mm
Track nominal width	406 mm
Track nominal length	3,923 mm
Track profile height	38.1 mm Charger

SUSPENSION

Front suspension	Dual A-arms
Front shock	Motion Control
Front suspension max. travel	210 mm
Rear suspension	SC™-5U
Center shock	Motion Control
Rear shock	HPG™
Rear suspension max. travel	239 mm

FEATURES

Frame	REV-XS™	Starter	Electric	Mirrors	Optional
Skis	Pilot™ DS 2	Reverse	Mechanical	Windshield	460 mm
Seating	2-up	Heated throttle lever	Standard	Runner	Square 3/8
Handlebar	Straight aluminum with J-hooks	Heated grips	Standard (driver only)	Carbide configuration	102 mm at 90°
Riser block height	160 mm	Gauge	Analog with display	Hitch	Tongue Type