

2019 GRAND TOURING SPORT

PACKAGE HIGHLIGHTS

- Rotax® 600 ACE™ engine with 650W magneto
- REV-XS™ platform
- SC™-5M rear suspension
- **381 x 3,487 x 31.8 mm (15 x 137 x 1.25 in.) RipSaw[†] track**
- Pilot™ DS 2 skis
- Brembo brake with braided stainless-steel brake line
- Excellent wind protection with a 450 mm windshield
- Steering controls module
- Mechanical reverse
- Heated passenger grips with air deflectors
- Reversible throttle lever (thumb or finger activated)
- Heated driver's visor power outlet
- Heavy duty rear bumper
- Air radiator with fan



ROTAX® ENGINE

600 ACE™

Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2
Displacement	600 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7,250 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	40 L
Oil tank capacity	2.1 L

POWERTRAIN

Drive clutch type	eDrive™ 2
Driven clutch type	QRS (short shaft)
Engagement	2,200 RPM
Small sprocket number of teeth	21
Large sprocket number of teeth	51
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm
Brake system	Brembo brake with stainless-steel braided brake line

DRY WEIGHT

234 kg

FEATURES

Frame	REV-XS™	Starter	Electric	Mirrors	Standard
Skis	Pilot™ DS 2	Reverse	Mechanical	Windshield	450 mm
Seating	2-up	Heated throttle lever	Standard	Runner	Round 1/2
Handlebar	Straight aluminum with J-hooks	Heated grips	Standard (driver and passenger)	Carbide configuration	102 mm at 90°
Riser block height	115 mm	Gauge	Analog with display	Hitch	EU type

COLOR

White ☐

DIMENSIONS

Vehicle overall length	3,000 mm
Vehicle overall width	1,217 mm
Vehicle overall height	1,275 mm
Ski stance	1,077 mm
Ski overall length	1,066 mm
Track nominal width	381 mm
Track nominal length	3,487 mm
Track profile height	31.8 mm RipSaw [†]

SUSPENSION

Front suspension	Dual A-arms
Front shock	Motion Control
Front suspension max. travel	220 mm
Rear suspension	SC™-5M
Center shock	Motion Control
Rear shock	HPG™
Rear suspension max. travel	245 mm