

2019 RENEGADE® SPORT

PACKAGE HIGHLIGHTS

- Rotax® 600 ACE™ engine with 420W magneto
- REV-XS™ platform
- SC™-5M rear suspension
- 381 x 3,487 x 31.8 mm (15 x 137 x 1.25 in.) Cobra† track
- HPG™ rear shock
- HPG™ Plus Aluminium front shocks
- Brembo brake with braided stainless-steel brake line
- Electric fuel gauge
- Straight aluminum handlebar with integrated J-hooks
- Comfortable REV-XP™ seat with 7 L of storage
- Standard electric start
- Mechanical reverse (600 ACE™)
- D.E.S.S.™ key
- Extended heat exchanger for better cooling capacity
- iTC™ Engine mapping modes (Standard, Sport or ECO®)
- Reversible throttle lever (thumb or finger activated)
- Heavy duty rear bumper



ROTAX® ENGINE

600 ACE™

Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2
Displacement	600 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7,250 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	40 L
Oil tank capacity	2.1 L

POWERTRAIN

Drive clutch type	eDrive™ 2
Driven clutch type	QRS (short shaft)
Engagement	2,200 RPM
Small sprocket number of teeth	21
Large sprocket number of teeth	51
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm
Brake system	Brembo brake with stainless-steel braided brake line

DRY WEIGHT

211 kg

COLOR

White / Orange Crush 

DIMENSIONS

Vehicle overall length	3,000 mm
Vehicle overall width	1,217 mm
Vehicle overall height	1,210 mm
Ski stance	1,077 mm
Ski overall length	1,066 mm
Track nominal width	381 mm
Track nominal length	3,487 mm
Track profile height	31.8 mm Cobra

SUSPENSION

Front suspension	Dual A-arms
Front shock	HPG Plus
Front suspension max. travel	220 mm
Rear suspension	SC™-5M
Center shock	HPG™
Rear shock	HPG
Rear suspension max. travel	245 mm

FEATURES

Frame	REV-XS™	Starter	Electric	Mirrors	Optional
Skis	Pilot™ DS 2	Reverse	Mechanical	Windshield	375 mm
Seating	REV-XP™ with storage	Heated throttle lever	Standard	Runner	Square 3/8
Handlebar	Straight aluminum with J-hooks	Heated grips	Standard	Carbide configuration	102 mm at 90°
Riser block height	115 mm	Gauge	Analog with display	Hitch	Optional